

Head Office

7 Factories Road
 South Geelong 3220
 Victoria Australia
 Email: gfirst@godfreyhirst.com
 www.godfreyhirst.com

Postal Address

PO Box 93
 Geelong 3220
 Victoria Australia
 Telephone: +61 (3) 5225 0222
 Facsimile: +61 (3) 5222 3885

PRODUCT	:	SUSSEX 40oz
DESCRIPTION	:	Tailored Level Loop
FIBRE TYPE	:	100% Selected carpet wools containing a proportion of wools classed as speciality types (Tolerance \pm 5%)
YARN CONSTRUCTION	:	Multiply Woollen Spun
TOTAL PILE WEIGHT	:	1360 gms/m ² - 40oz/yd ² (Tolerance \pm 5%)
PILE HEIGHT	:	5.0 mm (Tolerance \pm 1mm)
MACHINE GAUGE	:	31.5 per 100 mm - 1/8 th gauge (Non Staggered)
WIDTH	:	3.66 metres
PRIMARY BACKING	:	Woven Polypropylene
SECONDARY BACKING	:	Jute
A.C.C.S. RATING	:	Contract Heavy Duty & Stairs Residential Extra Heavy Duty & Stairs - Reg. No. 99130
RADIANT HEAT SOURCE AS ISO 9239.1.2003	:	CHF 9.7 kW/m ² [conventionally laid] Smoke Value 12% min
INDOOR AIR QUALITY	:	Total Volatile Organic Compounds (TVOC's) Emission level test results for this product comply with Green Label Plus criteria and Green Building Council requirements. (test results are available on request)
EXTRACTABLE MATTER Dichloromethane Extract A.S. 2001.3.4	:	1.5% Maximum
RESISTANCE TO INSECT PESTS A.S. 2001.6.1	:	Pass
TUFT WITHDRAWAL FORCE A.S. 2111.15	:	30 Newtons (minimum)
SECONDARY BACKING ADHESION A.S. 2111.16	:	40 Newtons (minimum)
COLOUR FASTNESS TO LIGHT B.S. 1006.B02	:	5-6 (Subject to colour selection)
COLOUR FASTNESS TO SHAMPOO A.S. 2111.19.2	:	3-4 minimum
COLOUR FASTNESS TO RUBBING A.S. 2111.19.1	:	3-4 [medium to light shades] 3 [dark shades]

www.godfreyhirst.com

When buying carpet always insist on an ACCS rated carpet.