

PRODUCT
Colours



100
GODDESS

Hybrid



180
BEAR

Hybrid



190
FOREST

Hybrid



300
NATURE

Hybrid



500
CHARIOT

Hybrid



510
ARCHER

Hybrid



520
DEER

Hybrid



540
ARROW

Hybrid



545
BLACKBUTT

Hybrid



555
SPOTTED GUM

Hybrid



560
HAWK

Hybrid



700
MOON

Hybrid



780
WILDERNESS

Hybrid



790
HUNTRESS

Hybrid

ARTEMIS

Artemis Hybrid flooring captures the natural beauty of timber with the best attributes of a laminate and vinyl floor. It is available in 14 stunning natural colours, reminiscent of the changing Australian landscape, and is built to withstand the extreme climatic changes of Australia. With Trigon® core technology and a UV coated surface you can confidently create a flawless look through all areas of your home.

Swatch colours are for guide purposes only.

PRODUCT

Specifications

ARTEMIS - Hybrid Product Details

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	5.5mm	Surface	Wood Grain Embossed
Wear Layer	0.55mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1513mm (L) x 223mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	7		
M ² per Box	2.362m ²	Backing Layer	1.5mm EVA
M ² per Pallet	106.29m ²	Profile	Micro Bevel
Colours	14	Protective Coating	UV Coating
Installation Method	Drop Lock		

Performance

Classification	23, 34, 42	ISO 10874
	Type 1	ISO 10582
Dimensional Stability	≤ 0.03%	ISO 23999
Thermal Resistance	0.05 m ² .K/W	EN 12667
Thermal Conductivity	0.1 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Residual Indentation	≤ 0.03mm	EN 425
Swelling After Submersion in Water	≤ 0%	ISO 24336
Castor Chair	No visible damage after 25000 revolutions	EN 425/ISO 4918
Impact Sound Reduction	Ln,W 53	ISO 10140-3
	IIC 56	ASTM E492-09
Light Fastness	≥ 6	EN ISO 105-B02
Chemical Resistance	Class 0, excellent	ISO 26987
	Class 0, excellent	ASTM F925
Flammability Rating	Available on Request	AS ISO 9239
Slip Resistance	Available on Request	AS/NZ 4586 - 2013
Residential Warranty*	Lifetime	
Commercial Warranty [†]	15 Years	

Sustainability

VOC Rating	DIBT Certified, REACH Compliant & CETEC
------------	---

Test results and certificates are available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Hybrid products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Hybrid Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

[†]Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

