

PRODUCT  
**Colours**



185  
IRON BARK

Hybrid  
Flooring



515  
TASSIE OAK

Hybrid  
Flooring



545  
BLACKBUTT

Hybrid  
Flooring



555  
SPOTTED  
GUM

Hybrid  
Flooring



625  
NORTHERN  
BOX

Hybrid  
Flooring



655  
FOREST RED

Hybrid  
Flooring



Swatch colours are for guide purposes only.

## NAPIER

Napier delivers astonishing durability and impact resistance. With innovative Trigon® Core Technology, this waterproof product remains stable in extreme temperatures and is ready to withstand an army of foot traffic.

## PRODUCT

# Specifications

## NAPIER- Hybrid Product Details

Technical Data			
Type	Hybrid	Finish	Matte
Plank Thickness	5.5mm	Surface	Embossed
Wear Layer	0.55mm	Profile	Micro Bevel
Dimensions	1813mm (L) x 144mm (W)	Top Layer	Decorative Film & Wear Layer
Planks per Box	9	Substrate Layer	Trigon® Core Technology (Limestone Composite)
M <sup>2</sup> per Box	2.35m <sup>2</sup>		
M <sup>2</sup> per Pallet	112.80m <sup>2</sup>	Backing Layer	1.5mm EVA
Colours	6	Protective Coating	UV Coating
Installation Method	Drop Lock		

## Performance

Classification	23, 34	ISO 10874
Dimensional Stability	≤ 0.03%	ISO 23999
Thermal Resistance	0.05 m <sup>2</sup> K/W	EN 12667
Thermal Conductivity	0.1 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Residual Indentation	≤ 0.03mm	EN 433 / ISO 24343-1
Swelling After Submersion in Water	0%	ISO 24336
Castor Chair	No Damage	EN 425
Impact Sound Reduction	Available on Request	ISO 10140-3 ASTM E492-09
Light Fastness	≥6	ISO 105-BO2
Chemical Resistance	Class 0, Excellent	EN 425
Flammability Rating	CRF 10.5/m <sup>2</sup> Smoke Value 170% minutes	AS ISO 9239
Slip Resistance	R10	AS / NZ 4586-2013
Residential Warranty*	Lifetime	
Commercial Warranty†	15 Years	

## Sustainability

VOC Rating	DIBT Certified, REACH Compliant & CETEC
------------	---

Test results and certificates are available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Hybrid products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Hybrid Installation Instructions.

\*Subject to proper installation and maintenance.

\*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

