

PRODUCT  
Colours



100  
PARCHMENT

Vinyl Plank



180  
FUMED  
OAK

Vinyl Plank



300  
AUTUMN  
OAK

Vinyl Plank



350  
CHESTNUT

Vinyl Plank



540  
RIVER  
OAK

Vinyl Plank



545  
BLACKBUTT

Vinyl Plank



550  
WESTERN  
TALLOWOOD

Vinyl Plank



555  
SPOTTED  
GUM

Vinyl Plank



655  
FOREST  
REDS

Vinyl Plank



710  
FROSTED  
OAK

Vinyl Plank



720  
SUMMIT  
OAK

Vinyl Plank



750  
CARBONISED  
OAK

Vinyl Plank



OLYMPUS <sup>DS</sup> VINYL PLANK


Combining durability, water resistance<sup>^</sup> and easy maintenance, the Olympus DS vinyl plank range is the perfect choice for home owners wanting a beautiful timber look that is suitable for all areas of the home. Godfrey Hirst vinyl plank is quiet underfoot, with a durable wear layer to provide protection against everyday wear and tear, making Olympus DS ideal for busy family homes.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. <sup>^</sup>Subject to proper installation and maintenance.

## PRODUCT

## Specifications

## OLYMPUS Direct Stick - Vinyl Plank Product Details

Technical Data		Technical Data	
Type	Vinyl Plank	Colours	12
Plank Thickness	2.5mm	Protective Coating	PUR + Scratch Resist + Stain Resist
Wear Layer	0.5mm	Finish	Matte
Dimensions	1219mm (L) x 184mm (W)	Surface	Embossed
Planks per Box	14	Profile	Micro Bevel
M <sup>2</sup> per Box	3.14m <sup>2</sup>	M <sup>2</sup> per Pallet	219.8m <sup>2</sup>
Installation Method	Direct Stick  Please refer Installation instructions for further details		



## Performance

Classification	23, 32	ISO 10582
Dimensional Stability	Length: 0.05% Width: 0.00% Curling: 0.00%	ISO 23999
Abrasion Rating	Group T	EN 660-2
Residual Indentation	0.03mm	ISO 24343-1
Castor Chair	No Damage	EN 425
Light Fastness	≤ 6	EN ISO 105-B02
Light Reflectiveness Values	100 Parchment 40.98% 350 Chestnut 28.92% 550 Western Tallowood 24.81% 710 Frosted Oak 36.55%	180 Fumed Oak 9.38% 540 River Oak 18.27% 555 Spotted Gum 18.5% 720 Summit Oak 24.79%
		300 Autumn Oak 32.79% 545 Blackbutt 36.21% 655 Forest Reds 18.46% 750 Carbonised Oak 18.55%
Slip Resistance	P2	AS/NZ 4586
Residential Warranty*	25 Years	
Commercial Warranty†	10 Years	
Reaction to Fire	TBC	EN ISO 9239
Suitable for wet areas	Yes - subject to proper installation and maintenance	
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide <a href="http://www.godfreyhirst.com">www.godfreyhirst.com</a> .	

## Sustainability

VOC Rating	Passes CETEC VOC test
Accreditation	Manufactured under a management system certified as complying with ISO 9001 & ISO14001

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

\*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.

Test results and certificates are available on request.