

PRODUCT
Colours



STOCKED*
FT-2201

Woven Vinyl



MADE TO ORDER
FT-2202

Woven Vinyl



MADE TO ORDER
FT-2203

Woven Vinyl



MADE TO ORDER
FT-2204

Woven Vinyl



MADE TO ORDER^
FT-2206

Woven Vinyl



MADE TO ORDER
FT-2207

Woven Vinyl



MADE TO ORDER^
FT-2208

Woven Vinyl



STOCKED*
FT-2209

Woven Vinyl



MADE TO ORDER^
FT-2210

Woven Vinyl



MADE TO ORDER
FT-2211

Woven Vinyl



MADE TO ORDER^
FT-2212

Woven Vinyl



KNIT

Cosy & Elegant

Knit has been designed for nostalgic homely appeal with its cosy and elegant finish. The pattern mimics similar knit structures of soft textiles to harmonies with other interior surfaces and furniture pieces in a space.

**Stocked in 500mm x 500mm x 3mm direct stick tile option (no minimum order).*

^176m² (1 pallet) minimum order / 9 week lead time.

All other Made to Order (MTO) 880m² (5 pallets) minimum / 12 week lead time.

Swatch colours are for guide purposes only.

PRODUCT

Specifications

KNIT (LOOM⁺) - Woven Vinyl Product Details

Technical Data

Type	Woven Vinyl	Protective Coating	EPT™ Shield Treatment (Anti-Bacterial)	
Colours	11 (2STK, 9MTO)	Installation Recommendation	Quarter Turn	

Available Options	Tile DS	Plank DS	Tile EL	Plank EL
Dimensions	500mm x 500mm	500mm x 1000mm	500mm x 500mm	500mm x 1000mm
Thickness	3.0mm	3.0mm	5.0mm	5.0mm
Quantity per Box	16 Tiles / 4.0m ²	8 Planks / 4.0m ²	10 Tiles / 2.5m ²	5 Planks / 2.5m ²
Installation Method	Direct Stick	Direct Stick	Express Lay	Express Lay
Stocked Option	2 Stocked 9 Made to Order	Made to Order	Made to Order	Made to Order

Performance	3.0mm DS	5.0mm EL	Standard
Classification	Commercial 33	Commercial 33	EN 685
Fraying	Frayproof	Frayproof	EN 1814
Thermal Performance	0.02m ² L/W	0.02m ² L/W	ISO 8302
Castor Chair	No Damage	No Damage	EN 985
Dimensional Stability	≤ 0.10% (Norm: ≤ 0.25%) Passed	≤ 0.10% (Norm: ≤ 0.15%) Passed	ISO 23999 EN 434 EN 986
Flammability Rating	CRF 10.6W/m ² Smoke Value 143% minutes	Available on Request	AS ISO 9239
Underfloor Heating	Suitable	Suitable	EN 12524
Light Fastness	≥ 6	≥ 6	ISO 105-B02
Slip Resistance	R10 / P3	R10 / P3	AS 4586
Flexibility	Passed	Passed	ISO 24344
Impact Sound Insulation	6dB	9dB	ISO 10140-3
Body Voltage	Fulfilled	Fulfilled	EN 1815
Squareness & Straightness	No Deviation ≤ 0.01 in	No Deviation ≤ 0.01 in	ISO 24342 ASTM F2055
Residual Indentation	≤ 0.01mm < 8%	≤ 0.01mm < 8%	ISO 24343-1 ASTM F1914
Resistance to Chemicals	No Defects No Defects	No Defects No Defects	ISO 26987 ASTM F925
Commercial Warranty*	Available on Request		
Sustainability	3.0mm DS	5.0mm EL	
VOC Rating	Passes CETEC VOC Test	Available on Request	



All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Woven Vinyl products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Woven Vinyl Installation Instructions.

Test results and certificates are available on request.