



**DESIGN**

Product Type:	Floating LVT
Overall Thickness:	3.2 mm (.13")
Wear Layer:	12 mil (0.3 mm)
Finish:	Enhanced Urethane
Size:	150mm x 1235mm (actual) 6" x 48"L (nominal)
Square Feet Per Carton:	31.9 sf/ctn
Pieces Per Carton:	16 pieces/ctn
Pounds per carton:	47.41 lbs/ctn
Installation Method:	Floating ERT with Uniclic Locking System
Recommended Adhesive:	None Required
Underlayment:	Mohawk ActiveSound

**PERFORMANCE**


Construction:	Light Commercial Grade Enhanced Resilient Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size and Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm)
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - 0.15% max (0.020 in. per linear foot)
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm <sup>2</sup> , Class 1
Smoke Density:	ASTM E662 - Passes - < 450

**SUSTAINABILITY**


Certification:	FloorScore® certified
----------------	-----------------------

**SERVICE**

Warranties:	Limited 6 Year Commercial Warranty
-------------	------------------------------------



233  
Gally Gold



242  
Honeytone



258  
Realist



262  
Pier



717  
Winter White



822  
Blondie



857  
Woodridge



872  
Bombay



881  
Armoire



988  
Key-Note