

Hot and Heavy Collection



DESIGN

Product Type:	Floating LVT
Overall Thickness:	5 mm (.2")
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force Ultra
Surface Profile:	Registered Emboss
Size:	228.6mm x 1516.9mm (actual) 9"W x 59"L (nominal)
Square Feet Per Carton:	22.4 sf/ctn (2.12 m2/ctn)
Pieces Per Carton:	6 pieces/ctn
Pounds per carton:	40.78 lbs/ctn (18.49 kg/ctn)
Installation Method:	Loose Lay with Perimeter Glue or Full Spread
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Adhesive

PERFORMANCE

Construction:	Commercial Grade Loose Lay Enhanced Resilient Tile
Classification:	ASTM F-1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 -10 Passes - maximum 0.010 in. (0.25mm)
Size and Tolerance:	ASTM F2055 - Passes - at ± 0.016 in./lin. Ft. (0.4 mm/305 mm)
Thickness:	ASTM F386 - Passes - as specified ± 0.005 in. (0.13 mm)
Flexibility:	ASTM F137 - Passes - 1 in. (25.4-mm mandrel, no crack or break)
Dimensional Stability:	ASTM F2199 - Passes - no greater than 0.020 in./lin. Ft. (0.51 mm/305 mm)
Static Load:	ASTM F970 - Passes - Exceeds 1000 psi
Residual Indentation:	ASTM F1914 - Passes - average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - no change
Resistance To Light:	ASTM F1515 - Passes - less than 8 ave., max
Resistance To Heat:	ASTM F1514 - Passes - less than 8 ave., max
Critical Radiant Flux:	ASTM E648 - Passes - > 0.45 watts/cm ² , Class 1

SUSTAINABILITY

Certification:	FloorScore® certified
----------------	-----------------------

SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------



132
Vera



138
Kingsley



241
Knox



322
Finn



358
Jackson



628
Lenox



758
Hermes



851
Butler



853
Emerson

Hot and Heavy Collection



958
Cole