

Molveno Collection

DESIGN

Product Type:	Floating LVT
Overall Thickness:	6 mm (.24")
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force Ultra
Size:	298.45mm x 908.05mm (actual) 11.75" W x 35.75" L (nominal)
Square Feet Per Carton:	17.503 sf/ctn
Pieces Per Carton:	6 pieces/ctn
Pounds Per Carton:	34.5 lbs/ctn
Installation Method:	Floating ERT with Unipush Locking System
Recommended Adhesive:	None Required

SUSTAINABILITY

Certification:	FloorScore® certified
Virgin Vinyl:	100% Virgin Vinyl

PERFORMANCE

Construction:	Commercial Grade Luxury Vinyl Tile
Squareness:	ASTM F2421 - Passes - $\pm 0.10"$ max
Size And Tolerance:	ISO 24337 - Plank @ 48" - Passes - $\pm 0.08"$
Thickness:	ASTM F387 - Passes - as specified $\pm 0.005"$
Dimensional Stability:	ASTM F2199 - Passes - 0.020"/linear foot max
Curling:	ASTM F2199 - Passes - 0.08" Max
Static Load:	ASTM F970 - Passes, modified at 1500 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%, maximum single reading 10%
Resistance To Chemicals:	ASTM F925 - Passes - No more than a slight change
Resistance To Light:	ASTM F1515 - Passes - $\Delta E < 8$
Resistance To Heat:	ASTM F1514 - Passes - $\Delta E < 8$
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 Part A - Less than 450
Wear Layer Thickness:	ASTM F410 - Passes - Commercial Min 0.02"

SERVICE

Warranties:	Limited 10 Year Commercial
-------------	----------------------------


879
Perfect Greige

889
Software

979
Grey Matters

988
Cityscape

997
Night Owl